ESIVES - AUTOMOTI ТМ E PRODUCTS

3M[™] SCOTCH-WELD[™] **URETHANE ADHESIVE DP605NS** A fast setting, urethane adhesive. Its non-sag prop-

erties make application on many vertical surfaces

easy. Has a 5 minute work life and is excellent for filling gaps. Adheres to wood, plastic and primed metal. Reaches handling strength in 15 to 20 minutes. 1.7 oz. Bottle. Color is off white.

P/N 09-01395.....

3M[™] SCOTCH-WELD[™] **EPOXY ADHESIVE 2216 B/A** A flexible, two part, room temperature cur-

ing epoxy with high peel and shear strength. Scotch-Weld epoxy adhesive 2216 B/A is identical to 3M[™] Scotch-Weld[™] Epoxy Adhesive EC-2216 B/A in chemical composition. Scotch-

Weld epoxy adhesive EC-2216 B/A has been labeled, packaged, tested, and certified for aircraft and aerospace applications. Scotch-Weld epoxy adhesive 2216 B/A may be used for aircraft and aerospace applications if proper Certificates of Test have been issued and material meets all aircraft manufacturer's specification requirements.

SIZE	COLOR	DESCRIPTION	PART NO.	PRICE
2 oz.	Gray	Adhesive 2216 B/A	02-00045	
Pint	Gray	Adhesive 2216 B/A	02-00113	
Quart	Gray	Adhesive 2216 B/A	02-00114	

3M[™] SCOTCH-WELD[™] INSTANT ADHESIVE CA40H

One-part, high strength, very fast setting adhesive cures at room temperature. Adheres to difficult to bond substrates such as EPDM rubber, aluminum, and flexible vinyl. Comes in a 1 oz. Bottle. Clear.

P/N 09-01368..... 3M[™] SCOTCH-WELD[™] **INSTANT ADHESIVE CA8**

This instant adhesive has a fast set time of 5 to 40 seconds. Excellent adhesion on metal, plastic and rubber. Bonds resist shock and impacts. A cyanoacrylate adhesive. Comes in a 1 oz. bottle.

P/N 09-01366.....



It is ideal for use with all 3M Cyanoacrylate Adhesives for a broad range of industrial and electronic applications. It is also ideal for use with CA-5, CA-9, or CA-50 Gel for many wire tacking and coil terminating applications. P/N 09-01407



3M SCOTCH-GRIP HP CON-TACT ADHESIVE

A high performance contact adhesive that provides a long bonding range and excellent initial strength

1357 Grey/OLIV..... P/N 09-01362..... 1357 Neutral 1G P/N 09-01373.....



PLASTIC ADHESIVE 2262 A clear, non-staining high strength adhesive with exceptional resistance to plasticizer migration. Develops tack

3M[™] SCOTCH-GRIP[™]

very rapidly. Can be used to bond many flexible, rigid and extruded vinyls to metal and many other surfaces. Comes P/N 09-01365..... in a 1 qt. can.



3M[™] SCOTCH GRIP **RUBBER ADHESIVE**

Lower viscosity, sprayable version of Scotch-Weld Neoprene High Performance Rubber and Gasket Adhesive 1300. Has excellent adhesion to metal, baked enamel, wood, most plastics, and neoprene, reclaim, SBR, and butyl rubber. not for EPDM rubber.

UPC	Size	Color	Part No.	Price
1300L	1 gt		09-27220	
1300L	Gallon.		09-01712	
1300L	5 Gallon		09-01713	
1300	5 oz.	YELLOW	09-01708	
1300	Quart		09-01709	
1300	Gallon		09-01710	
1300	5 Gallon		09-01711	



3M[™] SCOTCH-GRIP[™] **CONTACT ADHESIVE**

A brushable, neutral-colored contact adhesive for bonding many decorative laminates, aluminum, steel, plywood, panels, wood and wood veneer, masonry, rubber, canvas and other porous and non-porous materials to each other P/N 09-01364..... or to themselves.



3M[™] SCOTCH-GRIP[™] RUBBER AND GASKET ADHESIVE 847

This fast drying adhesive develops strength very quickly. It has excellent heat resistance; temperature performance is from -5 to 300F. Meets specification requirements of MIL-A-1154C. Bonds neoprene, reclaim, SB-R, and butyl rubber to metal, wood, most Bonds neoprene, reclaim, SB-K, and buty rubber to motal, wood, plastics, and many other products. 5oz. Tube. reddish Brown in Color. P/N 09-01361.....



3M[™] SCOTCH-SEAL[™] **DUCT SEALER**

An extremely smooth, easy handling knife or caulking grade sealant for sealing medium and high pressure heating and air conditioning ducts. P/N 09-01409.....



3M[™] GENERAL TRIM **ADHESIVE 8088 - CLEAR**

A high strength adhesive for bonding automotive materials (carpeting, jute pads, fabrics, plastics) to metal and other surfaces. Good heat and water resistance. Not recommended for bonding polystyrene foam. (For bonding polystyrene foam, use 3M™ Spray Trim Adhesive PN08074). 18.1 oz. can. Color is clear. P/N 09-01444.....

3M[™] IMPERIAL[™] HAND GLAZE

Non-silicone, non-wax hand glaze. Excellent depth of shine. Superior luster. Use by hand to refine and fill swirls after machine glazing refinish or factory applied paints. Specially formulated to work on all colors and can be painted over. 1 qt. Bottle. Color is clear. P/N 09-01438.....



3M[™] IMPERIAL[™] MACHINE GLAZE Non-silicone, non-wax machine glaze. Possesses excellent scratch removal characteristics. Superior depth of shine and luster. Use by machine to remove swirl marks after compounding acrylic lacquer. Formulated to work on all vehicle colors. 1 qt. bottle. Color is clear.

P/N 09-01439.....

3M[™] FINESSE-IT[™] **FINISHING MATERIAL 81235**

Specially designed compounds and polishes to be used on OEM and baked refinish paints to remove sand scratches or to remove swirl marks from previously compounded areas. P/N 09-01451..... 1at bottles



3M[™] FINESSE-IT[™] NATURAL BUFFING PAD

The 3 inch buffing pad is designed to get you into tight areas not accessible with a conventional polisher. Pads are hook-and-loop backed. Pads are sold P/N 09-01452..... each.



3M[™] PREMIUM LIQUID WAX

Clear coat safe wax. Use on all cured paint finishes. For use by hand or with an orbital polisher. Produces a high-gloss, deep-luster, durable finish on both new and used car paints. Special formulation is capable of removing road film or light oxidation from car finishes. Heavily oxidized finishes may require compounding with 3M™ Super Duty Rubbing Compound (PN39004) prior to ap-plying wax. P/N 09-01440..... plying wax.