

# LUBRICANTS

## LOCTITE THREADLOCKER



Loctite Threadlocker used on a standard fastener can eliminate expensive locking devices while you increase the reliability and quality of your assembly. One drop prevents loosening. 2 removable strengths for large & small applications and permanent strength for locking parts you never want to take apart.

- #222 Threadlocker (permanent, for small screws)  
10 ml..... P/N 09-42605..... 50 ml..... P/N 09-42610.....
- #242 Threadlocker (removable, for large screws)  
10 ml..... P/N 09-42615..... 50 ml..... P/N 09-42620.....
- #262 Threadlocker (permanent, for large screws)  
10 ml..... P/N 09-42625..... 50 ml..... P/N 09-42630.....

## PARKER-O-LUBE



Excellent for use on exposed valve plungers, cylinder rods, and other o-rings. It lubricates without causing deterioration of rubber and is water resistant. Good for low pressure vacuum and pneumatic systems.

- 4 oz. tube..... P/N 05-00773.....

## SEALUBE



Anti-seize sealer for threaded aluminum alloy parts exposed to gasoline, oil, water, air or vacuum. Good lubricating qualities. Will not harden or set. Will not freeze joints at low temperatures. Non-corrosive, insoluble in gasoline, oil or water.

- 1 Lb. Can ..... P/N 09-25200.....

## BAKERSEAL



Thread sealing and lubricating compound. Contains Teflon. Prevents thread leaks with fluids and gases up to 600°F. Recommended for gasoline and aircraft oils. Superior to Teflon tape and much easier to use. 8 oz. jar.

- P/N 09-00346.....

## LUBRIPLATE NO. 630AA



Multi-purpose lubricant. Forms a wearing film on working surfaces. Excellent protection against rust and corrosion. Recommended for controllable pitch props, wheel and magneto bearings, general greasing.

- 14 oz. Can..... P/N 09-25400.....
- 6 Lb.. Can..... P/N 09-25500.....

## EZ TURN LUBRICANT (FUELUBE)



EZ Turn is a specialty lubricant/sealant used for fuel and oil line valves and is resistant to high temperatures. It is especially effective where high octane fuels and aromatics are present. EZ Turn is also extremely efficient as a gasket paste and anti-seize agent. EZ Turn will not gum, crack or dry out. Each shipment is independently tested. Excellent for tapered plug valves, aircraft engine manufacturing, and marine applications. EZ Turn is the functional equivalent of fuel lube.

- 5 oz. tube..... P/N 09-00306.....
- 1 Lb. can..... P/N 09-00180.....

## PERMATEX ANTI-SEIZE LUBRICANT



Prevents galling, seizing and corrosion of metal parts from 65°F to 2000°F. Acts as a low speed lubricant and maintains a corrosion-resistant coating at high temperatures. Makes aluminum and stainless steel joints disassemble quickly, easily. Excellent lubricant for press fit assembly. Works on industrial engine parts, boilers, outdoor motors, cables and internal combustion engines. Conforms to MIL-A-907D. Improves reliability at high temperatures. Saves time, labor.

- 1 oz. tube ..... P/N 09-28410.....

## MICROLON PRECISION OILER



This oiler has the famous Microlon resin suspended in a light-weight oil to lubricate, penetrate and prevent rust. It is excellent for lubricating bearings, threaded parts, hinges, pocket knives, chains, rollers, fishing gear, chain saws, guns, garage doors..... just about anywhere that friction causes noise and resistance. Furnished in a handy pen size oiler with a pocket clip. .25 Fluid Ounces.

- P/N 09-00756.....

## WD-40 PENETRANT/LUBRICANT



Displaces moisture on any metal surface, preventing rust, corrosion or oxidation of the surface. Used on switches pulleys, wheel housings, seam areas. Non-gumming, non-conductive—safe for all electrical systems. Conforms to specification C-234

- 11. 12 oz. Spray ..... P/N 09-00347.....

## DRY GRAPHITE SPRAY NO. 5200



Provides a uniform dry lubricant film of non-abrasive graphite for any metal surface. Can be used alone or with fluid lubricants. Used in engine overhaul, on struts, gears, tracks. Meets MIL-G-26548. DGF-123

- 11 oz. Spray..... P/N 09-25600.....

## TRI-FLO TEFLON LUBRICANT



Penetrating lubricant with Teflon, corrosion inhibitors, moisture displacers and solvents to soften and remove dirt and corrosion. Will not cause corrosion. Use on aircraft cabin door hinges, landing gear hinges and struts. Loosens rusted bolts and other fasteners. 12oz. aerosol can

- P/N 09-42540.....

## FOAMING SUPERIOR LUBRICANT



Tri-Flow is revolutionizing the way you clean, protect and lubricate all of your moving parts with the introduction of Foaming Superior Lubricant and Foaming Citrus Cleaner Degreaser. Tri-Flow's powerful foaming action clings to both horizontal and vertical surfaces to allow for deep penetration and accurate application. Tri-Flow Foaming products are ideal for use on bicycles, firearms, sporting equipment, manufacturing equipment, and more!

- P/N 09-02082.....

## LIQUID WRENCH



A powerful blend of quick acting solvents to free parts frozen by rust, corrosion or paint. Harmless to metals. 11 oz. Aerosol

- Spray..... P/N 09-25800.....

## F-900 "TORQUE SEAL"



Inspection Lacquer is used in production on compression fittings, studs, nuts, parts, and assemblies after they are in proper torque or position. Widely used as "Anti-Sabotage Lacquer". Inspectors can visually detect any movement or tampering; Torque Seal becomes brittle and will crack. Excellent adhesion to all metals and to most other surfaces. Dries fast. Torque Seal is packaged in convenient 1/2 oz. poly squeeze tubes. Available in 4 high visibility.

- Yellow ..... P/N 09-25807.....
- Blue ..... P/N 09-25809.....
- Green ..... P/N 09-25808.....
- Orange..... P/N 09-25810.....
- Red ..... P/N 09-02033.....

## F-1000 SENTRY SEAL



Used on compression fittings, studs, nuts, parts and assemblies after they have been set to proper tension or position. Service personnel or inspectors can quickly spot any changes or tampering with equipment. Sentry Seal has excellent adhesion to metals, including aluminum, magnesium, titanium, stainless and copper, and is non-corrosive to these metals. It is packaged in handy metal tubes. Squeeze the tube to extrude the Sentry Seal through the small hole to form a bead (narrow stripe) across the parts. The surface dries in about one minute, then it will start to polymerize and become brittle as it dries completely. Available in blue.

- P/N 09-28512.....